

KONGKIM KK-1600&KK-1800

Digital Eco Solvent&Sublimation Inkjet Printer / 高精度数码写真机

Integrated structure beam, high strength and high resolution

3200dpi printer / 一体结构梁高精度高强度

• All New KK Series



| Technical Parameters | | | |
|-----------------------|--|------------------------|--------------------------|
| Model | KK-1600 | KK-1800 | |
| Maximun Print Size | 1650mm | 1850mm | |
| Head Number | 1/2 Optional | | |
| Head Type | XP600¹ | DX5¹ | i3200¹ |
| Resolution / Speed | 4Pass 12sqm/hr | 4Pass 16sqm/hr | 4Pass 24sqm/hr |
| | 6Pass 8sqm/hr | 6Pass 12sqm/hr | 6Pass 16sqm/hr |
| | 8Pass 6sqm/hr | 8Pass 8sqm/hr | 8Pass 12sqm/hr |
| Ink Type | Eco Solvent & Sublimation Inks | | |
| Ink System | Auto Ink Supply system | | |
| Media Type | Vinyl sticker,flex banner,backlit, window film,wall paper,Leather, Photo paper ... | | |
| Guide | THK linear guide | | |
| Motor | Leadshine integrated motor | | |
| Picture Type | PNG, JPG, JPEG, TIFF, PDF ... | | |
| Print Port | USB 2.0, USB3.0 | | |
| Operating System | Windows 7, Windows10, Windows 11 | | |
| RIP Software RIP | MainTop, PhotoPRINT | | |
| Power Supply | AC 220V&110V Optional 50/60HZ | | |
| Power | Print system: 0.5kw; Front heating 0.5kw; Rear heating 0.5kw; Back heating 1kw | | |
| Operation Environment | Tem: 18°C-28°C, Humidity: 40%RH-65%RH | | |
| Package Size&Weight | L*W*H: 2920*740*710mm/250KG | | |

MACHINE APPLICATIONS \ 机器的应用

