

KONGKIM KK-2513U

43 PLATFORM SUPPORT POINTS WITHOUT BLIND SPOTS

+NETHERLANDS PRINT FACTORY /MAINTOP COLOR MANAGEMENT SOFTWARE

IMPORTED 750W AC SERVO MOTOR + DOUBLE Y AXIS IMPORTED 400W AC SERVO

MOTORMULTI-FACE MILLING INTEGRATED ALUMINUM BEAM + LG LED-UV LAMP CURING SYSTEM



Glass



Acrylic



Ceramic

Technical Parameters

Brand	KONGKIM		Resolution	Max 720x1800dpi	
Model	KK-2513U		Print-Head	RICOH G5/G6 print-head optional	
Print Size	2500mm *1300mm		Color	CMYK+W+V+Lc+Lm (optional)	
Ink	RICOH GEN6 special UV ink		Ink prompt	Real-time display of ink quantity	
Printing Speed	Print Head	4 Rows of Ricoh G5 print-heads		4 Rows of Ricoh G6 print-heads	
	Print Mode	4PASS	6PASS	8PASS	4PASS 6PASS 8PASS
	All Color Mode	60m ² /h	40m ² /h	30m ² /h	90m ² /h 60m ² /h 45m ² /h
	C+W Mode	30m ² /h	21m ² /h	16m ² /h	45m ² /h 31m ² /h 24m ² /h
Print Material	KT board, PVC board, acrylic, metal plate, aluminum plastic board, foam board, mobile phone case tiles...				
Ink Supply	Independent secondary ink cartridge constant temperature continuous ink supply				
RIP Software	PrintFactory and MainTop RIP software optional				
Drive System	High power AC servo computer [X/Y/Z axis]				
Control System	BYHX board, the most stable print control system in China				
ICC Profile	Gb calibration ICC color adjustment function				
Curing System	Korea LG LED-UV		Print Platform	Zone 4 vacuum platform	
Negative Pressure system	White、Colorindependent negative pressure system		Print thickness	100mm/Max 100mm	
Print Port	USB3.0/USB2.0		Picture format	Tif、JPG、PNG、BMP、PDF、PSD...	
OS	WIN 7/WIN 10 / WIN 11 64bit		Power Supply	AC 220V(±10%) 50/60HZ ,4KW	
Humiture	18°C~28°C/30%RH~65%RH		Machine Weight	NW1000KG, GW 1200KG	
Machine Size	L*W*H:4100*2060*1400mm		Packing Size	L*W*H:4450*2150*1700mm	